





1 2 3 4 5 6 7 8 9 10 11 12 13 14 15

Pin#	FtA	FtB	FtC
2x5	10.16	21.68	31.90
2x6	12.70	24.22	34.44
2x7	15.24	26.76	36.98
2x8	17.78	29.30	39.52
2x9	20.32	31.84	42.06
2x10	22.86	34.38	44.60
2x11	25.40	36.92	47.14
2x12	27.94	39.46	49.68
2x13	30.48	42.00	52.22
2x14	33.02	44.54	54.76
2x15	35.56	47.08	57.30
2x16	38.10	49.62	59.84
2x17	40.64	52.16	62.38
2x18	43.18	54.70	64.92
2x19	45.72	57.24	67.46
2x20	48.26	59.78	70.00
2x21	50.80	62.32	72.54
2x22	53.34	64.86	75.08
2x23	55.88	67.40	77.62
2x24	58.42	69.94	80.16
2x25	60.96	72.48	82.70
2x26	63.50	75.02	85.24
2x27	66.04	77.56	87.78
2x28	68.58	80.10	90.32
2x29	71.12	82.64	92.86
2x30	73.66	85.18	95.40
2x31	76.20	87.72	97.94
2x32	78.74	90.26	100.48
2x33	81.28	92.80	103.02
2x34	83.82	95.34	105.56
2x35	86.36	97.88	108.10
2x36	88.90	100.42	110.64
2x37	91.44	102.96	113.18
2x38	93.98	105.50	115.72
2x39	96.52	108.04	118.26
2x40	99.06	110.58	120.80



技术规范:
 额定电流 : 3AMP
 适用温度 : -40°C to +105°C
 接触电阻 : 20mΩ Max
 绝缘电阻 : 1000MΩ Min
 耐电压 : AC 1000V
 绝缘材料 : Polyester (UL94V-0)
 Standard: PBT
 端子材质 : Brass
 电镀规范 : Au or Sn Over 50u" Ni

插接系列	间距	插孔	双排	单排	Pin数	绝缘	材质	角度	端子	备注
c-1	0.8mm		1-单排	1-单排	1"	1"0P/50P	A-PBT	S-90°	12.5mm间距25	0-3.0
b-1	1.0mm		2-双排	2-单排	2"	2"0P/50P	B-SL	R-90°	11.0mm间距18	1-3.0/0.6 (双排)
c-1	1.27mm		3-三排	3-三排	3"	3"0P/50P	C-PBT	R-90°	12.5mm间距22	2-3.0/0.3 (双排)
d-2	1.0mm		4-四排	4-四排	4"	4"0P/50P	D-PBT	L-90°	100#-带焊接端子	3-2.8/0.4 (双排)
e-2	1.0mm						B-150°	B-150°	100#-带焊接端子	4-2.6/0.3 (双排)
f-2	1.5mm						F-90°	F-90°	100#-带焊接端子	其它另做说明
f-3	1.5mm						S-90°		100#-带焊接端子	
h-5	1.0mm						H-半封装			

F	a	10	1	2	5p	a	a	s	D	0
插接系列	间距	插孔	双排	单排	Pin数	绝缘	材质	角度	端子	备注

STC 上海狮拓电子科技有限公司

THIRD ANGLE PROJECTION

客户确认: 姓名, 日期, 日期, 日期, 日期, 日期, 日期, 日期

2.54mm间距牛角, 180°, 立高19.0mm
 Spec: 2.54mm Female Header, Dual Row, Straight
 Positions: 2x5"2x40
 Plastics Height: 19.0mm