







6613F-02





6613F-3×03





6613F-03





6613F-2×02





6613F-3×04



6613F-04



6613F-2×03



6613F-3×05

技术参数 SPECIFICATIONS

- ◆ 间距: 4.5 Pitch:4.5
- ◆ 适用线规: AWG#26-#16
Applicable Wire:AWG#26-#16
- ◆ 额定电压: AC,DC, 300V (有效值)
Voltage rating: AC,DC, 300V(rms)
- ◆ 额定电流: 6.0-10.0A, AC, DC
Current rating:6.0-10.0A, AC, DC
- ◆ 耐压值: 1500V AC/minute
Withstand voltage:1500V AC/minute
- ◆ 工作温度: -25℃~+85℃
Working Temp:-25℃~+85℃
- ◆ 绝缘电阻: ≥1500Ω
Insulation resistance:≥1500Ω
- ◆ 接触电阻: ≤15mΩ
Contact resistance:≤15mΩ

材料 MATERIAL

- ◆ 绝缘体: 尼龙66, UL94V-0
Insulator:Nylon66 UL94V-0

TOLERANCE:	
X. ±XXX	
.X ±0.20	
.XX ±0.10	
ANG.	

	上海狮拓电子科技有限公司
	产品名稱: _____ 产品料號: _____
THIRD ANGLE PROJECTION	

簽名 _____	客戶確認 <input type="checkbox"/> 承認 _____ 日期 _____ <input type="checkbox"/> 駁回 _____ 日期 _____
日期 _____	
審核 _____	
日期 _____	

EL-NA